

Exinda Network Orchestrator 2061 is the perfect branch office appliance for small and medium businesses. Architected for branch networks, the 2061 delivers the best price-performance in the category. Network managers who need improved performance for business-critical applications will find the perfect combination of application acceleration and bandwidth control at a reasonable price point. One of our most popular appliances, the 2061 is the most innovative small branch network solution on the market today.

Network Diagnostics	Base	Expanded
Max APS Objects	20	40
Max SLA Objects	10	20
Max PDF Reports	4	20

Traffic Shaping	Base	Expanded
Max Shaping Throughput	10 Mbps	10 Mbps
Max Concurrent Flows	32,000	32,000
Max New Connections Rate	30/s	30/s
Max Traffic Policies	128	256

Traffic Acceleration	Base	Expanded
Max Acceleration Throughput	6 Mbps	6 Mbps
Max Edge Cache Throughput	50 Mbps	50 Mbps
Max Accelerated Connections	300	600

Interface Capabilities	
Built in NICs	2 bypass bridge pairs GigE
Additional NIC Slots	None
Management Ports	RJ45 Serial Console, dedicated management GigE NIC
IPMI	Not Present

Physical Characteristics	
Form Factor	desktop unit with optional rackmount kit
Dimensions (HxWxD)	44 mm x 215.5 mm x 190 mm, 1.73" x 8.48" x 7.48"
Power	external power brick, auto-ranging, field replaceable
Power Consumption	54W @ 0.43A (under load)
Weight	0.2 kg, 2.64 lbs. (including external power brick)
Data Store / Cache Size	240 GB
Environment	0°C to 40°C operating temp, 5%-90% operating humidity
Number of VMs supported	0