

Exinda Network Orchestrator 8062 is our fastest growing product line and is designed for true data center scale. This network orchestration appliance provides monitoring and control that scales to support bandwidth up to 5 Gbps. Popular with mid and large size enterprises and education institutions with rapidly growing users, devices, apps and activities across all network locations. Built to scale, the Exinda 8062 makes it easy to protect application SLAs during high volume peak hours as well as control recreational traffic and streaming video.

Network Diagnostics	Base	Expanded
Max APS Objects	200	300
Max SLA Objects	200	300
Max PDF Reports	75	100

Traffic Shaping	Base	Expanded
Max Shaping Throughput	5 Gbps	5 Gbps
Max Concurrent Flows	5,000,000	5,000,000
Max New Connections Rate	15,000/s	15,000/s
Max Traffic Policies	2048	4096

Traffic Acceleration	Base	Expanded
Max Acceleration Throughput	155 Mbps	155 Mbps
Max Edge Cache Throughput	900 Mbps	900 Mbps
Max Accelerated Connections	10,000	16,000

Interface Capabilities	
Built in NICs	None
Additional NIC Slots	4
Available NICs	10 bridge GigE copper 6 bridge GigE fiber (LC connector) 3 bridge 10GE copper or fiber (LC connector)
Management Ports	DB15 Serial Console and dedicated management and cluster GigE NIC
IPMI	Present – shared with dedicated management NIC

Physical Characteristics	
Form Factor	2U rackmount with included sliding rails
Dimensions (HxWxD)	86.8 mm x 434 mm x 684 mm, 3.42" x 17.09" x 26.93"
Power	Dual redundant internal – auto ranging and field replaceable
Power Consumption	370W @ 2.8A (under load)
Weight	28.2 kg, 62.04 lbs.
Data Store / Cache Size	2.7 TB, RAID 10 redundancy
Environment	10°C to 35°C operating temp, 10%-80% operating humidity
Number of VMs supported	2 w/ 4GB RAM, 4 w/ 2GB RAM